

SRK-YYSH-WF SINGLE-SPLIT WALL MOUNTED TYPE

3 YEARS Warranty



SRK10,13,18YYSH-WF



Wireless remote control



BUILT IN WIRELESS LAN



Made in Thailand



SRK24YYSH-WF



SRC10YYSH-W



SRC13YYSH-W



SRC18YYSH-W



SRC24YYSH-W

FUNCTIONS

ENERGY SAVING

AIR FLOW



CLEAN OPERATION & FILTER



COMFORT & CONVENIENCE



OTHERS




SPECIFICATIONS

SPECIFICATIONS			1 HP	1.5 HP	2 HP	3 HP	
Indoor unit			SRK10YYSH-WF	SRK13YYSH-WF	SRK18YYSH-WF	SRK24YYSH-WF	
Outdoor unit			SRC10YYSH-W	SRC13YYSH-W	SRC18YYSH-W	SRC24YYSH-W	
Power source			1 Phase, 220 - 240V, 50Hz				
Nominal cooling capacity (Min-Max)		kW	2.0 (0.9 - 2.9)	2.5 (0.9 - 3.1)	3.5 (0.9 - 4.0)	5.0 (1.3 - 5.5)	
Nominal heating capacity (Min-Max)		kW	2.7 (0.9 - 4.3)	3.2 (0.9 - 4.5)	4.0 (0.9 - 5.0)	5.8 (1.3 - 6.6)	
Power consumption	Cooling/Heating	kW	0.44 / 0.59	0.62 / 0.74	0.89 / 0.94	1.35 / 1.56	
EER/COP	Cooling/Heating		4.55 / 4.58	4.03 / 4.32	3.93 / 4.26	3.70 / 3.72	
Max. running current		A	9	9	9	14.5	
Sound power level	Indoor	Cooling/Heating	48 / 50	50 / 53	54 / 56	59 / 60	
	Outdoor	Cooling/Heating	56 / 56	56 / 58	61 / 61	61 / 63	
Sound pressure level	Indoor	Cooling (Hi/Me/Lo/Ulo)	34 / 25 / 22 / 19	36 / 28 / 23 / 19	40 / 30 / 26 / 19	46 / 36 / 29 / 22	
		Heating (Hi/Me/Lo/Ulo)	36 / 29 / 23 / 19	39 / 30 / 24 / 19	41 / 36 / 25 / 19	46 / 37 / 31 / 24	
	Outdoor	Cooling/Heating	45 / 45	46 / 46	50 / 48	51 / 52	
Air flow	Indoor	Cooling (Hi/Me/Lo/Ulo)	9.3 / 7.0 / 5.9 / 5.0	9.9 / 8.0 / 5.9 / 5.0	11.3 / 8.7 / 7.0 / 5.0	12.1 / 9.9 / 7.4 / 5.9	
		Heating (Hi/Me/Lo/Ulo)	10.0 / 8.5 / 6.5 / 5.9	11.3 / 8.7 / 6.7 / 5.9	12.3 / 11.0 / 7.0 / 5.6	13.9 / 11.2 / 9.1 / 7.4	
	Outdoor	Cooling/Heating	27.4 / 23.6	27.4 / 23.6	31.5 / 27.8	32.8 / 32.8	
Exterior dimensions	Indoor	Height x Width x Depth	mm	290 x 870 x 230			
	Outdoor			540 x 780(+62) x 290		595 x 780(+62) x 290	
Net weight	Indoor / Outdoor		kg	9.5 / 31.0		9.5 / 34.5	10.0 / 36.0
Refrigerant		Type/GWP	kg/TCO ₂ Eq	R32 / 675		1.05 / 0.709	
		Charge		0.62 / 0.419			
Refrigerant piping size		Liquid/Gas	ø mm	6.35(1/4") / 9.52(3/8")		6.35(1/4") / 12.7(1/2")	
Refrigerant line (one way) length [chargeless length]			m	Max.20 [15]		Max.25 [15]	
Vertical height differences		Outdoor is higher/lower	m	Max.10 / Max.10		Max.15 / Max.15	
Outdoor operating temperature range		Cooling	°CDB	-15 to 46			
		Heating		-15 to 24			
Clean filter			Allergen Clear Filter x1, Photocatalytic Washable Deodorising Filter x1				

* The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

* Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

* The above specifications are subject to change without prior notice.



Wo Kee Hong Limited

Hong Kong Office



+ 852 2514 4700



Unit 3302, 33/F, Cable TV Tower,
9 Hoi Shing Road, Tsuen Wan, N.T., H.K.



wokeehong-mhi.com.hk

Macau Office



+ 853 2876 8155



Rua de S. Domingos No. 16F-16L, Centro
Comercial, Hin Lei 5 Audar 63 Room, Macau



info@wokeehong.com.hk



Website



Warranty
Registration


SRK63,71,80,100ZRH-WF

**BUILT IN
WIRELESS LAN**

**Wireless
remote control**

Made in Thailand

SRK63ZRH-W
SRK71,80ZRH-W, FDC100VNPH-W

FUNCTIONS

ENERGY SAVING



AIR FLOW



CLEAN OPERATION & FILTER



COMFORT & CONVENIENCE



OTHERS



SPECIFICATIONS

				2.5 HP	3 HP	3.5 HP	4 HP
Indoor unit				SRK63ZRH-WF	SRK71ZRH-WF	SRK80ZRH-WF	SRK100ZRH-WF
Outdoor unit				SRC63ZRH-W	SRC71ZRH-W	SRC80ZRH-W	FDC100VNPH-W
Power source				1 Phase, 220 - 240V, 50Hz			
Nominal cooling capacity (Min-Max)		kW		6.3 (1.2 - 7.4)	7.1 (2.3 - 7.8)	8.0 (2.3 - 9.7)	9.6 (2.1 - 9.6)
Nominal heating capacity (Min-Max)		kW		7.1 (0.8 - 9.3)	8.0 (2.0 - 10.8)	9.0 (2.1 - 11.2)	10.0 (1.7 - 10.4)
Power consumption		Cooling/Heating	kW	1.63 / 1.64	1.93 / 1.95	2.09 / 2.27	3.10 / 2.80
EER/COP		Cooling/Heating		3.87 / 4.33	3.68 / 4.10	3.83 / 3.96	3.10 / 3.57
Max. running current			A	14.5	17	17	19
Sound power level	Indoor	Cooling/Heating		56 / 58	57 / 60	60 / 62	63 / 63
	Outdoor	Cooling/Heating	dB(A)	64 / 65	63 / 63	67 / 67	68 / 67
Sound pressure level	Indoor	Cooling (Hi/Me/Lo/Ulo)		44 / 39 / 35 / 25	44 / 41 / 37 / 25	47 / 44 / 39 / 26	48 / 45 / 40 / 27
	Outdoor	Heating (Hi/Me/Lo/Ulo)	dB(A)	44 / 38 / 34 / 28	46 / 39 / 35 / 28	47 / 41 / 36 / 29	48 / 43 / 38 / 30
Air flow	Indoor	Cooling/Heating		54 / 54	53 / 51	56 / 55	56 / 54
	Outdoor	Cooling (Hi/Me/Lo/Ulo)	m ³ /min	20.5 / 18.1 / 15.7 / 10.4	20.5 / 18.6 / 16.2 / 10.4	23.5 / 20.2 / 17.5 / 10.4	24.5 / 21.3 / 17.6 / 10.4
Exterior dimensions	Indoor	Heating (Hi/Me/Lo/Ulo)	m ³ /min	22.5 / 19.0 / 16.5 / 13.1	25.0 / 19.8 / 17.3 / 13.3	26.5 / 21.3 / 18.4 / 13.5	27.5 / 23.2 / 19.1 / 13.6
	Outdoor	Cooling/Heating		41.5 / 41.5	55 / 43.5	63 / 49.5	63 / 55
Net weight	Indoor / Outdoor	Height x Width x Depth	mm	640 x 800(+71) x 290	339 x 1197 x 262	750 x 880(+88) x 340	16.5 / 57.0
			kg	15.5 / 45.0	15.5 / 56.0	16.5 / 57.0	
Refrigerant				R32 / 675			
Type/GWP							
Charge		kg/TCO ₂ Eq		1.25 / 0.844	1.5 / 1.013	1.6 / 1.080	1.7 / 1.148
Refrigerant piping size		Liquid/Gas	ø mm	6.35(1/4") / 12.7(1/2")		6.35(1/4") / 15.88(5/8")	
Refrigerant line (one way) length [chargeless length]		m			Max.30 [15]		
Vertical height differences		Outdoor is higher/lower	m		Max.20 / Max.20		
Outdoor operating temperature range		Cooling	°CDB		-15 to 46		
		Heating			-15 to 24		
Clean filter				Allergen Clear Filter x1, Photocatalytic Washable Deodorising Filter x1			

* The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

* Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

* The above specifications are subject to change without prior notice.



SRK-ZSXH-WF SINGLE-SPLIT WALL MOUNTED TYPE

3 YEARS
Warranty



SRK20,25,35,50,60ZSXH-WF



BUILT IN
WIRELESS LAN



Made in Thailand



Wireless
remote control



SRC20,25,35,50,60ZSXH-W

FUNCTIONS

ENERGY SAVING



AIR FLOW



COMFORT & CONVENIENCE



CLEAN OPERATION & FILTER



OTHERS




SPECIFICATIONS

SPECIFICATIONS			3/4 HP	1 HP	1.5 HP	2 HP	2.5 HP	
Indoor unit			SRK20ZSXH-WF	SRK25ZSXH-WF	SRK35ZSXH-WF	SRK50ZSXH-WF	SRK60ZSXH-WF	
Outdoor unit			SRC20ZSXH-W	SRC25ZSXH-W	SRC35ZSXH-W	SRC50ZSXH-W	SRC60ZSXH-W	
Power source			1Phase, 220 - 240V, 50Hz					
Nominal cooling capacity (Min-Max)		kW	2.0 (0.9 - 3.4)	2.5 (0.9 - 3.8)	3.5 (0.9 - 4.5)	5.0 (1.0 - 6.2)	6.1 (1.0 - 6.9)	
Nominal heating capacity (Min-Max)		kW	2.7 (0.8 - 5.5)	3.2 (0.8 - 6.0)	4.3 (0.8 - 6.8)	6.0 (0.8 - 8.2)	6.8 (0.8 - 8.8)	
Power consumption	Cooling/Heating	kW	0.31 / 0.47	0.44 / 0.59	0.74 / 0.90	1.24 / 1.36	1.71 / 1.65	
EER/COP	Cooling/Heating		6.45 / 5.74	5.68 / 5.42	4.73 / 4.78	4.03 / 4.41	3.57 / 4.12	
Max. running current		A	9	9	9	15	15	
Sound power level	Indoor	Cooling/Heating	53 / 55	55 / 56	58 / 58	59 / 62	62 / 63	
	Outdoor	Cooling/Heating	56 / 58	57 / 58	61 / 62	63 / 61	65 / 64	
Sound pressure level	Indoor	Cooling (Hi/Me/L0/Ulo) Heating (Hi/Me/L0/Ulo)	38 / 31 / 24 / 19 38 / 33 / 25 / 19	39 / 33 / 25 / 19 40 / 34 / 27 / 19	43 / 35 / 26 / 19 42 / 35 / 28 / 19	44 / 39 / 31 / 22 47 / 41 / 33 / 23	48 / 41 / 33 / 22 47 / 42 / 34 / 23	
	Outdoor	Cooling/Heating	43 / 45	44 / 45	48 / 47	51 / 49	52 / 53	
Air flow	Indoor	Cooling (Hi/Me/L0/Ulo) Heating (Hi/Me/L0/Ulo)	11.3 / 9.1 / 6.0 / 5.0 12.2 / 10.3 / 7.2 / 5.4	12.2 / 10.0 / 6.7 / 5.0 12.8 / 11.0 / 7.8 / 5.4	13.1 / 10.8 / 7.3 / 5.0 13.9 / 11.8 / 8.6 / 5.4	14.3 / 12.4 / 7.8 / 5.4 17.3 / 14.3 / 9.8 / 6.2	16.3 / 13.4 / 8.9 / 5.4 17.8 / 13.7 / 10.9 / 6.2	
		Outdoor	Cooling/Heating	31.0 / 31.0	31.0 / 31.0	36.0 / 31.0	39.0 / 33.0	41.5 / 39.0
	Exterior dimensions	Indoor Outdoor	Height x Width x Depth	305 x 920 x 220 640 x 800(+71) x 290				
Net weight	Indoor / Outdoor		kg	13.0 / 43.0			13.0 / 45.0	
Refrigerant		Type/GWP	R32 / 675					
		Charge	kg/TCO ₂ Eq	1.20 / 0.810				
Refrigerant piping size	Liquid/Gas		ø mm 6.35(1/4") / 9.52(3/8")				6.35(1/4") / 12.7(1/2")	
Refrigerant line (one way) length [chargeless length]		m	Max.25 [15]					Max.30 [15]
Vertical height differences		Outdoor is higher/lower	m	Max.15 / Max.15			Max.20 / Max.20	
Outdoor operating temperature range	Cooling	°CDB	-15 to 46					
	Heating		-20 to 24					
Clean filter			Allergen Clear Filter x1, Photocatalytic Washable Deodorising Filter x1					

* The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

* Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

* The above specifications are subject to change without prior notice.



Wo Kee Hong Limited

Hong Kong Office



+ 852 2514 4700



Unit 3302, 33/F, Cable TV Tower,
9 Hoi Shing Road, Tsuen Wan, N.T., H.K.



wokeehong-mhi.com.hk

Macau Office



+ 853 2876 8155



Rua de S. Domingos No. 16F-16L, Centro
Comercial, Hin Lei 5 Audar 63 Room, Macau



info@wokeehong.com.hk



Website



Warranty
Registration


SRK20,25,35,50ZSH-WF

**BUILT IN
WIRELESS LAN**

**Wireless
remote control**

SRC20,25,35ZSH-W

SRC50ZSH-W

Made in Thailand

FUNCTIONS

ENERGY SAVING



AIR FLOW



CLEAN OPERATION & FILTER



COMFORT & CONVENIENCE



OTHERS



SPECIFICATIONS

			3/4 HP	1 HP	1.5 HP	2 HP
Indoor unit			SRK20ZSH-WF	SRK25ZSH-WF	SRK35ZSH-WF	SRK50ZSH-WF
Outdoor unit			SRC20ZSH-W	SRC25ZSH-W	SRC35ZSH-W	SRC50ZSH-W
Power source			1 Phase, 220 - 240V, 50Hz			
Nominal cooling capacity (Min-Max)		kW	2.0 (0.9 - 2.9)	2.5 (0.9 - 3.1)	3.5 (0.9 - 4.0)	5.0 (1.3 - 5.5)
Nominal heating capacity (Min-Max)		kW	2.7 (0.9 - 4.3)	3.2 (0.9 - 4.5)	4.0 (0.9 - 5.0)	5.8 (1.3 - 6.6)
Power consumption		kW	0.44 / 0.59	0.62 / 0.74	0.89 / 0.94	1.35 / 1.56
EER/COP						
Cooling/Heating			4.55 / 4.58	4.03 / 4.32	3.93 / 4.26	3.70 / 3.72
Max. running current		A	9	9	9	14.5
Sound power level	Indoor	Cooling/Heating	48 / 50	50 / 53	54 / 56	59 / 60
	Outdoor	Cooling/Heating	56 / 56	56 / 58	61 / 61	61 / 63
Sound pressure level	Indoor	Cooling (Hi/Me/Lo/Ulo)	34 / 25 / 22 / 19	36 / 28 / 23 / 19	40 / 30 / 26 / 19	46 / 36 / 29 / 22
		Heating (Hi/Me/Lo/Ulo)	36 / 29 / 23 / 19	39 / 30 / 24 / 19	41 / 36 / 25 / 19	46 / 37 / 31 / 24
	Outdoor	Cooling/Heating	45 / 45	46 / 46	50 / 48	51 / 52
Air flow	Indoor	Cooling (Hi/Me/Lo/Ulo)	9.3 / 7.0 / 5.9 / 5.0	9.9 / 8.0 / 5.9 / 5.0	11.3 / 8.7 / 7.0 / 5.0	12.1 / 9.9 / 7.4 / 5.9
		Heating (Hi/Me/Lo/Ulo)	10.0 / 8.5 / 6.5 / 5.9	11.3 / 8.7 / 6.7 / 5.9	12.3 / 11.0 / 7.0 / 5.6	13.9 / 11.2 / 9.1 / 7.4
	Outdoor	Cooling/Heating	27.4 / 23.6	27.4 / 23.6	31.5 / 27.8	32.8 / 32.8
Exterior dimensions	Indoor	Height x Width x Depth	290 x 870 x 230			
	Outdoor		540 x 780(+62) x 290			
Net weight		kg	9.5 / 31.0		9.5 / 34.5	10.0 / 36.0
Refrigerant	Type/GWP		R32 / 675			
	Charge	kg/TCO ₂ Eq	0.62 / 0.419		0.78 / 0.527	1.05 / 0.709
Refrigerant piping size		Liquid/Gas	6.35(1/4") / 9.52(3/8")			
Refrigerant line (one way) length [chargeless length]		m	Max.20 [15]			
Vertical height differences		Outdoor is higher/lower	Max.10 / Max.10			
Outdoor operating temperature range	Cooling	°CDB	-15 to 46			
	Heating		-15 to 24			
Clean filter			Allergen Clear Filter x1, Photocatalytic Washable Deodorising Filter x1			

* The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

* Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

* The above specifications are subject to change without prior notice.

